


Galvanized Earth Rod

[Amiable Impex](#) manufactures Galvanized Earth Rod in India. Earthing Rods is also known as Ground Rod

Galvanized Earth Rod is made from low carbon steel with a high tensile strength of at least 600 N/mm². Low carbon steel core are molecularly tended with 99.9% pure electrolytic copper.

Dimension Rod Size (DIA x LENGTH)	Length in feet	Actual Rod Dia "S"	Thread Dia "T"	Product Code
9.5 x 1200 (UN - THREADED)	4	9.5	-	GER - 012
9.5 x 1800 (UN - THREADED)	6	9.5	-	GER - 018
14 x 1200	4	12	14	GER - 1412
14 x 1500	5	12	14	GER - 1415
14 x 1800	6	12	14	GER - 1418
14 x 2000	6.66	12	14	GER - 1420
14 x 2400	8	12	14	GER - 1424
5/8" x 4' or 16mm x 1200	4	14.2	5/8"	GER - 112
5/8" x 5' or 16mm x 1500	5	14.2	5/8"	GER - 115
5/8" x 6' or 16mm x 1800	6	14.2	5/8"	GER - 118
5/8" x 8' or 16mm x 2400	8	14.2	5/8"	GER - 124
5/8" x 10' or 16mm x 3000	10	14.2	5/8"	GER - 130
5/8" x 4' or 16mm x 1200	4	16	5/8"	GER - 312
5/8" x 5' or 16mm x 1500	5	16	5/8"	GER - 315
5/8" x 6' or 16mm x 1800	6	16	5/8"	GER - 318
3/4" x 4' or 19mm x 1200	4	17.2	3/4"	GER - 212
3/4" x 5' or 19mm x 1500	5	17.2	3/4"	GER - 215
3/4" x 6' or 19mm x 1800	6	17.2	3/4"	GER - 218
3/4" x 8' or 19mm x 2400	8	17.2	3/4"	GER - 224
3/4" x 10' or 19mm x 3000	10	17.2	3/4"	GER - 230



Salient Features of Galvanized Earth Rod

- Perfectly bonded Galvanized Earth Rod will last longer, drive easier and will not crack.
- The Galvanized Earth Rod will without any cracks, holes, cavities etc.
- Threads are rolled by roll threading process, which ensures that when copper covers is maintained, at the root of the thread, Roll thread gives greater strength than cut thread.
- Thread rolling process raises the surface of the rod so that Thread dia. (T) is greater than (S)
- Magnetic conducting rate is low. Thus reducing the lightning induction.
- Good tensile strength in Galvanized Earth Rod, over 600N/mm².
- Resist corrosion allowing for a 20-year service life in most soils
- Corrosion resistance while providing the lowest resistance to ground.

We can supply Galvanized Earth Rod in all sizes and shapes, threaded and/ or tipped.

- 1) Galvanized Earth Rod can be made double heads thread, thread can be packed by plastic sheath
- 2) One end is pointed and the other end is threaded for extend
- 3) One end is pointed and the other end is flat.

*Special sizes and copper thickness can be supplied on request

Packaging: We maintain Export Sea worthy packing i.e. it firstly packed in Plastic Packing with Thread protection in PVC Cap and then into Hard PVC Plastic pack. We also pack in wooden Packing on request.



Even though many of our products are standard items and of Standard BS Grade, we also make special tailor made products made exactly to the requirements of our customers in terms of Material Grade and Size.

An [Earthing Rods / Ground Rod](#) is an array of electrodes which is installed in the ground to provide a low resistance electrical path to ground or earth. In electrical engineering, ground or earth is the reference point in an electrical circuit from which other voltages are being measured or it is common return path for electric current or a direct physical connection to the Earth.

Electrical circuits may be connected to ground / earth for several reasons. In mains powered equipment, exposed metal parts are connected to ground or earth to prevent contact with a dangerous voltage if electrical insulation fails. Connections to ground, limit the build-up of static electricity when handling flammable products or electrostatic-sensitive devices.

For measurement purposes, the Earth serves as a reasonably constant potential reference against which other potentials can be measured. An electrical grounding / earthing system should have an appropriate current-carrying capability to serve as an adequate zero-voltage reference level.

In electronic circuit theory, a "ground" is usually idealized as an infinite source or sinks for charge, which can absorb an unlimited amount of current without changing its potential. Where a real ground connection has a significant resistance, the approximation of zero potential is no longer valid. Stray voltages or earth / ground potential rise effects will occur, which may create noise in signals or if large enough will produce an electric shock hazard. We have all the expertise needed in developing & manufacturing special types of Earthing Rods as per customers design, size, specifications and different types of coating or microns as required. For more details please visit our website: www.earth-rod.com OR www.amiableimpex.com

Our Other products in Copper Bonded Earthing Rods / Earthing Rods

S. no.	INDEX
01	Copper Bonded Earthing Rods or Grounding Rods
02	Earthing Rods or Earthing Rods
03	Copper Bonded Earthing Rods 15 to 25 microns
04	100 microns Copper Bonded Earthing Rods
05	Copper Clad Earthing Rods in 150 microns
06	Copper Clad Earthing Rods of 250 microns
07	Copper Clad Earthing Rods 350 microns
08	Solid Copper Bonded Earthing Rods - Pure Copper Rod
09	Stainless Steel Earthing Rods
10	Galvanized coated Earthing Rods
11	Threaded Earthing Rods
12	Earthing Rods Clamp
13	Earthing Rods Clamps
14	Earthing Rods Coupler

Regd. Office -

AMIABLE IMPEX.

101/A, Surya Darshan, Pai Nagar,
Borivali(W), Mumbai – 400092. **India.**
Phone: 022-28933996 / 022-28957101
Fax: 022-28957102



AMIABLE IMPEX

Plot No.495, Rohitvas,
Motapondha, Vapi-396191
Gujarat,India.

Contact Person -

MAULIK SHAH

E-mail: maulik@amiableimpex.com
Mob :+ 91- 9594899995

UJJWAL SHAH

E-mail: ujjwal@amiableimpex.com
Tel :+ 91- 22-28933996



Website: www.amiableimpex.com

www.earth-rod.com